NSN 5950-01-149-1114

Power Transformer - Page 1 of 2

Reliability Indicator:



View Online at https://aerobasegroup.com/nsn/5950-01-149-1114

| Not established |
|---|
| Overall Length: |
| 9.750 inches |
| Center To Center Distance Between Mounting Facilities Parallel To Length: |
| 8.120 inches all mounting facilities all center groupings |
| Center To Center Distance Between Mounting Facilities Parallel To Width: |
| 4.500 inches all mounting facilities all center groupings |
| Overall Height: |
| 10.380 inches |
| Overall Width: |
| 6.250 inches |
| Mounting Slot Width: |
| 0.280 inches all groupings |
| Frequency Rating: |
| 50.0 hertz single component or 60.0 hertz single component |
| Input-output Phase Relationship: |
| Single phase to single phase single component |
| Maximum Transformer Power Rating: |
| 5.0 kilovolt-ampere single component |
| Winding Shielding Method: |
| Internally shielded single component |
| Inclosure Type: |
| Fully enclosed |
| Mounting Facility Quantity: |
| 4 2nd group |
| Mounting Method: |
| Bracket all groupings and slot all groupings |
| Winding Function And Quantity: |
| 1 primary single component and 2 secondary single component |
| Winding Operating Current: |
| 1.2 amperes dc single component 1st secondary |
| Winding Operating Voltage: |
| 500.00 dc volts single component 2nd secondary |
| Terminal Type And Quantity: |
| 9 tab, solder lug |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |

NSN 5950-01-149-1114

Power Transformer - Page 2 of 2



Fiig:

A058b0