

View Online at <https://aerobasegroup.com/nsn/5950-01-149-6929>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

12.360 inches single mounting facility single center group and 12.400 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

10.230 inches single mounting facility single center group and 10.270 inches single mounting facility single center group

Mounting Hole Diameter:

0.420 inches single group and 0.460 inches single group

Frequency Rating:

47.0 hertz single component and 63.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internal shield grounded to core and brought out to terminal single component

Body Length:

13.500 inches

Body Width:

12.870 inches

Body Height:

10.750 inches

Maximum Operating Temp:

155.0 degrees celsius

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Unthreaded hole single group

Winding Function And Quantity:

1 primary single component and 1 secondary single component

Winding Operating Current:

104.3 amperes ac single component single secondary

Winding Power Rating:

12.0 k1lovolt-amperes single component single secondary

Winding Operating Voltage:

230.00 ac pounds per hour wet single component single primary

Terminal Type And Quantity:

5 threaded stud

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0