

View Online at <https://aerobasegroup.com/nsn/5950-01-150-6452>

Reliability Indicator:

Not established

Overall Length:

Between 3.813 inches and 3.938 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

2.969 inches single mounting facility single center group and 3.031 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

2.407 inches single mounting facility single center group and 2.469 inches single mounting facility single center group

Overall Height:

Between 5.375 inches and 5.687 inches

Overall Width:

Between 3.250 inches and 3.375 inches

Frequency Rating:

50.0 hertz single component and 65.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internal shield grounded to core single component

Maximum Operating Temp:

130.0 degrees celsius

Inclosure Type:

Hermetically sealed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded stud single group

Winding Function And Quantity:

1 primary single component and 2 secondary single component

Thread Size:

0.190 inches single group

Winding Operating Current:

8.5 amperes ac single component all secondary

Winding Operating Voltage:

20.00 ac volts single component all secondary

Thread Series Designator:

Unf single group

Terminal Type And Quantity:

6 wire hook

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0