

View Online at <https://aerobasegroup.com/nsn/5950-01-150-6453>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

3.250 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

3.500 inches single mounting facility single center group

Frequency Rating:

60.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Maximum Transformer Power Rating:

0.5 kilovolt-ampere single component

Body Length:

6.500 inches

Body Width:

4.000 inches

Body Height:

4.750 inches

Inclosure Type:

Partially enclosed, double shell

Mounting Facility Quantity:

4 single group

Mounting Method:

Bracket single group and unthreaded hole single group

Winding Function And Quantity:

1 primary single component and 2 secondary single component

Winding Operating Current:

4.16 amperes ac single component 3rd secondary

Winding Operating Voltage:

220.00 ac pounds per hour dry single component single primary and 480.00 ac pounds per hour with retaining chain single component single primary

Cognizant Service:

Usn

Unpackaged Unit Weight (non-core):

11.500 pounds

Terminal Type And Quantity:

6 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0