NSN 5950-01-152-0151

Power Transformer - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5950-01-152-0151

| Dummy Terminal Quantity (non-core): |
|---|
| 1 |
| Reliability Indicator: |
| Not established |
| Frequency Rating: |
| 47.0 hertz single component |
| Input-output Phase Relationship: |
| Single phase to single phase single component |
| Maximum Transformer Power Rating: |
| 43.0 volt-ampere single component |
| Winding Shielding Method: |
| Internal shield brought out to terminal single component |
| Body Length: |
| 3.125 inches |
| Body Width: |
| 3.000 inches |
| Body Height: |
| 2.500 inches |
| Distance Between Mounting Facility Centers: |
| 2.625 inches single mounting facility single center group |
| Inclosure Type: |
| Fully enclosed |
| Mounting Facility Quantity: |
| 2 single group |
| Mounting Method: |
| Bracket single group and slot single group |
| Winding Function And Quantity: |
| 1 primary single component and 2 secondary single component |
| Winding Operating Current: |
| 410.0 milliamperes ac single component single primary |
| Winding Operating Voltage: |
| 115.00 ac pounds per hour wet single component single primary |
| Terminal Type And Quantity: |
| 7 tab, solder lug |
| Shelf Life: |
| |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A058b0 |