

View Online at <https://aerobasegroup.com/nsn/5950-01-152-1913>

**Reliability Indicator:**

Not established

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

2.660 inches single mounting facility single center group

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

2.500 inches single mounting facility single center group

**Mounting Slot Width:**

0.203 inches single group

**Frequency Rating:**

48.0 hertz single component and 420.0 hertz single component

**Input-output Phase Relationship:**

Single phase to single phase single component

**Winding Shielding Method:**

Internally shielded single component

**Body Length:**

3.260 inches

**Body Width:**

3.260 inches

**Body Height:**

3.840 inches

**Maximum Operating Temp:**

105.0 degrees celsius

**Inclosure Type:**

Partially enclosed, double shell

**Mounting Facility Quantity:**

4 single group

**Mounting Method:**

Slot single group

**Winding Function And Quantity:**

2 primary single component and 2 secondary single component

**Winding Operating Current:**

4.5 amperes dc single component 1st secondary

**Winding Operating Voltage:**

38.20 ac volts single component 2nd secondary

**Terminal Type And Quantity:**

11 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A058b0