

View Online at <https://aerobasegroup.com/nsn/5950-01-153-8267>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.995 inches single mounting facility single center group and 2.005 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.620 inches single mounting facility single center group and 1.630 inches single mounting facility single center group

Frequency Rating:

48.0 hertz single component and 60.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internal shield grounded to inclosure single component

Body Length:

Between 2.565 inches and 2.690 inches

Body Width:

Between 2.125 inches and 2.250 inches

Body Height:

Between 4.375 inches and 4.500 inches

Maximum Operating Temp:

155.0 degrees celsius

Inclosure Type:

Hermetically sealed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded stud single group

Winding Function And Quantity:

1 primary single component and 3 secondary single component

Thread Size:

0.190 inches single group

Winding Operating Current:

750.0 milliamperes ac single component 3rd secondary

Winding Power Rating:

65.0 volts-amperes single component 2nd secondary

Winding Operating Voltage:

6.30 ac volts single component 3rd secondary

Thread Series Designator:

Unf single group

Terminal Type And Quantity:

12 turret

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0