

View Online at <https://aerobasegroup.com/nsn/5950-01-153-9392>

Reliability Indicator:

Not established

Turn Quantity:

200 single component single winding

Center To Center Distance Between Mounting Facilities Parallel To Length:

2.000 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.630 inches single mounting facility single center group

Overall Height:

2.484 inches

Inductance Type:

Swinging

Inductance Rating:

17.00 millihenries single component single winding and 42.00 millihenries single component single winding

Frequency Rating:

120.0 hertz single component

Body Length:

2.500 inches

Body Width:

2.125 inches

Body Height:

2.125 inches

Maximum Operating Temp:

130.0 degrees celsius

Winding Quantity:

1 single component

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded hole single group

Rating Method:

Electrical single component single winding and winding turns single component single winding

Thready Qty Per Inch (tpi):

32 single group

Thread Size:

0.138 inches single group

Winding Conductor Size:

0.03589 inches american wire gage single component single winding

Winding Operating Current:

1.0 amperes dc single component single winding and 2.5 amperes dc single component single winding

Dc Resistance Rating In Ohms:

0.630 single component single winding

Criticality Code Justification:

Zzzy

Special Features:

Item must comply with requirements of defense supply center columbus production standard no. Lo3277

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

2 standoff, solder lug

Reference Number Differentiating Characteristics:

Reference number differentiating material will be in accordance with naval inventory control point activity hx quality control. Manufacturing and testing specifications available at the dla icp

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0