

View Online at <https://aerobasegroup.com/nsn/5950-01-154-2391>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

2.850 inches single mounting facility single center group and 2.890 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

2.480 inches single mounting facility single center group and 2.520 inches single mounting facility single center group

Mounting Slot Width:

0.160 inches single group and 0.200 inches single group

Frequency Rating:

57.0 hertz single component and 63.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internal shield grounded to inclosure single component

Body Length:

3.500 inches

Body Width:

3.250 inches

Body Height:

Between 3.830 inches and 3.870 inches

Maximum Operating Temp:

130.0 degrees celsius

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Slot single group

Winding Function And Quantity:

1 primary single component and 2 secondary single component

Winding Operating Current:

50.0 milliamperes dc single component 1st secondary

Winding Operating Voltage:

67.50 ac volts single component 2nd secondary

Terminal Type And Quantity:

8 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0