## NSN 5950-01-154-2391

Power Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-01-154-2391

## **Reliability Indicator:** Not established Center To Center Distance Between Mounting Facilities Parallel To Length: 2.850 inches single mounting facility single center group and 2.890 inches single mounting facility single center group Center To Center Distance Between Mounting Facilities Parallel To Width: 2.480 inches single mounting facility single center group and 2.520 inches single mounting facility single center group **Mounting Slot Width:** 0.160 inches single group and 0.200 inches single group **Frequency Rating:** 57.0 hertz single component and 63.0 hertz single component Input-output Phase Relationship: Single phase to single phase single component Winding Shielding Method: Internal shield grounded to inclosure single component **Body Length:** 3.500 inches **Body Width:** 3.250 inches **Body Height:** Between 3.830 inches and 3.870 inches **Maximum Operating Temp:** 130.0 degrees celsius Inclosure Type: Fully enclosed **Mounting Facility Quantity:** 4 single group **Mounting Method:** Slot single group Winding Function And Quantity: 1 primary single component and 2 secondary single component Winding Operating Current: 50.0 milliamperes dc single component 1st secondary Winding Operating Voltage: 67.50 ac volts single component 2nd secondary **Terminal Type And Quantity:** 8 tab, solder lug Shelf Life: N/a Unit Of Measure: **Demilitarization:** No

## **NSN 5950-01-154-2391** Power Transformer - Page 2 of 2

Fiig: A058b0

