

View Online at <https://aerobasegroup.com/nsn/5950-01-154-4455>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

2.312 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

2.500 inches single mounting facility single center group

Mounting Slot Width:

0.312 inches single group

Frequency Rating:

50.0 hertz single component or 60.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Maximum Transformer Power Rating:

1.0 kilovolt-ampere single component

Body Length:

7.187 inches

Body Width:

5.812 inches

Body Height:

6.812 inches

Maximum Operating Temp:

85.0 degrees celsius

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Slot single group

Winding Function And Quantity:

1 primary single component and 2 secondary single component

Winding Operating Current:

8.7 amperes ac single component 3rd secondary

Winding Operating Voltage:

220.00 ac volts single component single primary and 440.00 ac volts single component single primary

Special Features:

Primary fuse blocks and secondary fuse kits available

Terminal Type And Quantity:

6 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0