NSN 5950-01-154-4768

Reactor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-01-154-4768

Delich litter bediester.
Reliability Indicator:
Not established
Hazardous Locations/environmental Protection:
Moisture resistant and vibration resistant
Overall Length:
1.209 inches
Turn Quantity:
22-1/2 single component single winding
Mounting Hole Diameter:
0.147 inches single group
Inductance Type:
Fixed
Inductance Rating:
202.50 microhenries single component single winding
Frequency Rating:
1.0 kilohertz single component
Overall Diameter:
1.209 inches
Maximum Operating Temp:
125.0 degrees celsius
End Application:
Aircraft f-18
Winding Quantity:
1 single component
Inclosure Type:
Open
Mounting Facility Quantity:
1 single group
Mounting Method:
Unthreaded hole single group
Rating Method:
Electrical single component single winding and winding turns single component single winding
Winding Conductor Size:
0.04030 inches american wire gage single component single winding
Winding Operating Current:
4.0 amperes dc single component single winding
Dc Resistance Rating In Ohms:
0.047 single component single winding
Test Data Document:

93322-7109257 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.;

excludes any specification, standard or other document that may be referenced in a basic governing drawing)

2 turret

Terminal Type And Quantity:

NSN 5950-01-154-4768

Reactor - Page 2 of 2



_			•		
•	n	ο.	•	18	e:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0