

View Online at <https://aerobasegroup.com/nsn/5950-01-154-4770>

**Reliability Indicator:**

Not established

**Hazardous Locations/environmental Protection:**

Moisture resistant

**Overall Length:**

0.788 inches

**Turn Quantity:**

35-1/2 single component single winding

**Mounting Hole Diameter:**

0.120 inches single group

**Inductance Type:**

Fixed

**Inductance Rating:**

202.00 microhenries single component single winding

**Frequency Rating:**

1.0 kilohertz single component

**Overall Diameter:**

Between 0.693 inches and 0.717 inches

**Maximum Operating Temp:**

125.0 degrees celsius

**End Application:**

Aircraft f-18

**Winding Quantity:**

1 single component

**Inclosure Type:**

Open

**Mounting Facility Quantity:**

1 single group

**Mounting Method:**

Unthreaded hole single group

**Rating Method:**

Electrical single component single winding and winding turns single component single winding

**Features Provided:**

Tinned wire leads

**Winding Conductor Size:**

0.02010 inches american wire gage single component single winding

**Winding Operating Current:**

2.0 amperes dc single component single winding

**Dc Resistance Rating In Ohms:**

0.170 single component single winding

**Test Data Document:**

93322-7109257 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

**Terminal Type And Quantity:**

2 turret

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A058b0