

View Online at <https://aerobasegroup.com/nsn/5950-01-154-4770>

Reliability Indicator:

Not established

Hazardous Locations/environmental Protection:

Moisture resistant

Overall Length:

0.788 inches

Turn Quantity:

35-1/2 single component single winding

Mounting Hole Diameter:

0.120 inches single group

Inductance Type:

Fixed

Inductance Rating:

202.00 microhenries single component single winding

Frequency Rating:

1.0 kilohertz single component

Overall Diameter:

Between 0.693 inches and 0.717 inches

Maximum Operating Temp:

125.0 degrees celsius

End Application:

Aircraft f-18

Winding Quantity:

1 single component

Inclosure Type:

Open

Mounting Facility Quantity:

1 single group

Mounting Method:

Unthreaded hole single group

Rating Method:

Electrical single component single winding and winding turns single component single winding

Features Provided:

Tinned wire leads

Winding Conductor Size:

0.02010 inches american wire gage single component single winding

Winding Operating Current:

2.0 amperes dc single component single winding

Dc Resistance Rating In Ohms:

0.170 single component single winding

Test Data Document:

93322-7109257 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Terminal Type And Quantity:

2 turret

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0