## NSN 5950-01-154-4770

Reactor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-01-154-4770

Reliability Indicator:
Not established
Hazardous Locations/environmental Protection:
Moisture resistant
Overall Length:
0.788 inches
Turn Quantity:
35-1/2 single component single winding
Mounting Hole Diameter:
0.120 inches single group
Inductance Type:
Fixed
Inductance Rating:
202.00 microhenries single component single winding
Frequency Rating:
1.0 kilohertz single component
Overall Diameter:
Between 0.693 inches and 0.717 inches
Maximum Operating Temp:
125.0 degrees celsius
End Application:
Aircraft f-18
Winding Quantity:
1 single component
Inclosure Type:
Open
Mounting Facility Quantity:
1 single group
Mounting Method:
Unthreaded hole single group
Rating Method:
Electrical single component single winding and winding turns single component single winding
Features Provided:
Tinned wire leads
Winding Conductor Size:
0.02010 inches american wire gage single component single winding
Winding Operating Current:
2.0 amperes dc single component single winding
Dc Resistance Rating In Ohms:
0.170 single component single winding
Test Data Document:

93322-7109257 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

## NSN 5950-01-154-4770

Reactor - Page 2 of 2



Terminal Type And Quantity:
2 turret
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A058b0