

View Online at <https://aerobasegroup.com/nsn/5950-01-155-4778>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

2.125 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.750 inches single mounting facility single center group

Frequency Rating:

400.0 hertz single component

Input-output Phase Relationship:

Three phase to three phase single component

Transformer Winding Connection Type:

Wye-wye

Body Length:

2.750 inches

Body Width:

2.375 inches

Body Height:

3.812 inches

End Application:

Arleigh burke class ddg; missile system, aegis surface (sms) mk 7; guided missile launching system, mk 26 (gmls); ticonderoga class cg (47)

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded stud single group

Winding Function And Quantity:

1 primary, fixed autotransformer type single component

Thread Size:

0.138 inches single group

Winding Operating Current:

320.0 milliamperes ac single component single primary input

Criticality Code Justification:

Feat

Winding Operating Voltage:

57.50 ac volts single component single primary output

Special Features:

Weapon system essential

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

6 solder stud

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0