# NSN 5950-01-155-7043

Power Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-01-155-7043

# **Reliability Indicator:**

Not established

#### Center To Center Distance Between Mounting Facilities Parallel To Length:

2.484 inches single mounting facility single center group and 2.516 inches single mounting facility single center group

#### **Center To Center Distance Between Mounting Facilities Parallel To Width:**

2.047 inches single mounting facility single center group and 2.079 inches single mounting facility single center group

#### **Overall Height:**

2.500 inches

#### **Frequency Rating:**

50.0 hertz single component and 440.0 hertz single component

#### Input-output Phase Relationship:

Single phase to single phase single component

#### Winding Shielding Method:

Internal shield grounded to core single component

#### **Body Length:**

Between 2.984 inches and 3.016 inches

#### **Body Width:**

Between 2.953 inches and 2.985 inches

# **Inclosure Type:**

Open

# **Mounting Facility Quantity:**

4 single group

#### **Mounting Method:**

Threaded hole single group

# **Winding Function And Quantity:**

2 primary single component and 3 secondary single component

# **Features Provided:**

Color coded lead and w/overload protection

# Thread Size:

0.164 inches single group

# **Winding Operating Current:**

30.0 milliamperes dc single component 1st secondary

# **Winding Power Rating:**

29.44 volts-amperes single component 3rd secondary

#### Winding Operating Voltage:

92.00 dc volts single component 3rd secondary

#### **Special Features:**

Terminal tied to one end of fuse

# **Thread Series Designator:**

Unc single group

# **Terminal Type And Quantity:**

12 wire lead

# NSN 5950-01-155-7043

Power Transformer - Page 2 of 2



_					
c	hο	JIF.		.ife:	
J			_	.II C.	

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A058b0