NSN 5950-01-155-7043

Power Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-01-155-7043

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

2.484 inches single mounting facility single center group and 2.516 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

2.047 inches single mounting facility single center group and 2.079 inches single mounting facility single center group

Overall Height:

2.500 inches

Frequency Rating:

50.0 hertz single component and 440.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internal shield grounded to core single component

Body Length:

Between 2.984 inches and 3.016 inches

Body Width:

Between 2.953 inches and 2.985 inches

Inclosure Type:

Open

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded hole single group

Winding Function And Quantity:

2 primary single component and 3 secondary single component

Features Provided:

Color coded lead and w/overload protection

Thread Size:

0.164 inches single group

Winding Operating Current:

30.0 milliamperes dc single component 1st secondary

Winding Power Rating:

29.44 volts-amperes single component 3rd secondary

Winding Operating Voltage:

92.00 dc volts single component 3rd secondary

Special Features:

Terminal tied to one end of fuse

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

12 wire lead

NSN 5950-01-155-7043

Power Transformer - Page 2 of 2



_					
c	hο	JIF.		.ife:	
J			_	.II C.	

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0