

View Online at <https://aerobasegroup.com/nsn/5950-01-156-4955>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

5.320 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

4.280 inches single mounting facility single center group

Overall Width:

6.360 inches

Mounting Slot Width:

0.390 inches single group

Frequency Rating:

48.0 hertz single component and 420.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Maximum Transformer Power Rating:

2.65 kilovolt-ampere single component

Winding Shielding Method:

Internal shield brought out to terminal single component

Body Length:

6.570 inches

Maximum Operating Temp:

55.0 degrees celsius

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Bracket single group and slot single group

Winding Function And Quantity:

2 primary single component and 1 secondary single component

Winding Operating Current:

22.0 amperes dc single component single secondary

Winding Operating Voltage:

93.00 ac volts single component 2nd primary and 105.00 ac volts single component 2nd primary and 115.00 ac volts single component 2nd primary and 125.00 ac volts single component 2nd primary

Terminal Type And Quantity:

11 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0