

View Online at <https://aerobasegroup.com/nsn/5950-01-156-4955>

**Reliability Indicator:**

Not established

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

5.320 inches single mounting facility single center group

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

4.280 inches single mounting facility single center group

**Overall Width:**

6.360 inches

**Mounting Slot Width:**

0.390 inches single group

**Frequency Rating:**

48.0 hertz single component and 420.0 hertz single component

**Input-output Phase Relationship:**

Single phase to single phase single component

**Maximum Transformer Power Rating:**

2.65 kilovolt-ampere single component

**Winding Shielding Method:**

Internal shield brought out to terminal single component

**Body Length:**

6.570 inches

**Maximum Operating Temp:**

55.0 degrees celsius

**Inclosure Type:**

Fully enclosed

**Mounting Facility Quantity:**

4 single group

**Mounting Method:**

Bracket single group and slot single group

**Winding Function And Quantity:**

2 primary single component and 1 secondary single component

**Winding Operating Current:**

22.0 amperes dc single component single secondary

**Winding Operating Voltage:**

93.00 ac volts single component 2nd primary and 105.00 ac volts single component 2nd primary and 115.00 ac volts single component 2nd primary and 125.00 ac volts single component 2nd primary

**Terminal Type And Quantity:**

11 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A058b0