NSN 5950-01-158-7197

Power Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-01-158-7197

| Reliability Indicator: |
|---|
| Not established |
| Overall Length: |
| 1.875 inches |
| Center To Center Distance Between Mounting Facilities Parallel To Length: |
| 1.426 inches single mounting facility single center group |
| Center To Center Distance Between Mounting Facilities Parallel To Width: |
| 0.881 inches single mounting facility single center group |
| Overall Height: |
| 1.500 inches |
| Overall Width: |
| 1.406 inches |
| Frequency Rating: |
| 45.0 hertz single component and 450.0 hertz single component |
| Input-output Phase Relationship: |
| Single phase to single phase single component |
| Inclosure Type: |
| Fully enclosed |
| Mounting Facility Quantity: |
| 4 single group |
| Mounting Method: |
| Threaded hole single group |
| Winding Function And Quantity: |
| 1 primary single component and 1 secondary single component |
| Thready Qty Per Inch (tpi): |
| 32 single group |
| Thread Size: |
| 0.138 inches single group |
| Winding Operating Current: |
| 3.0 milliamperes ac single component single secondary |
| Winding Operating Voltage: |
| 208.00 ac volts single component all winding |
| Thread Series Designator: |
| Unc single group |
| Terminal Type And Quantity: |
| 4 pin |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |

No

NSN 5950-01-158-7197

Power Transformer - Page 2 of 2



Fiig:

A058b0