NSN 5950-01-158-9100

Power Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-01-158-9100

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

4.562 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

2.000 inches single mounting facility single center group

Mounting Slot Width:

0.218 inches single group

Frequency Rating:

50.0 hertz single component or 60.0 hertz single component

Input-output Phase Relationship:

Three phase to six phase single component

Transformer Winding Connection Type:

Delta-wye

Winding Shielding Method:

Internal shield grounded to core single component

Body Length:

6.250 inches

Body Width:

5.500 inches

Body Height:

4.750 inches

Maximum Operating Temp:

32.0 degrees celsius

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Bracket single group and slot single group

Winding Function And Quantity:

1 primary single component and 1 secondary single component

Winding Operating Current:

16.3 amperes ac single component single secondary

Winding Operating Voltage:

208.00 ac volts single component single primary

Special Features:

Neutral tap on secondary brought out to two terminals

Terminal Type And Quantity:

11 eyelet

Shelf Life:

N/a

NSN 5950-01-158-9100

Power Transformer - Page 2 of 2



| ш | ın | 10 | <i>(</i>)+ | Measure: | |
|---|----|----|-------------|----------|--|
| | | | | | |

--

Demilitarization:

No

Fiig:

A058b0