

View Online at <https://aerobasegroup.com/nsn/5950-01-159-5561>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

4.610 inches single mounting facility single center group and 4.630 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

4.930 inches single mounting facility single center group and 4.950 inches single mounting facility single center group

Mounting Slot Width:

0.240 inches single group and 0.300 inches single group

Frequency Rating:

57.0 hertz single component and 63.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internal shield grounded to inclosure single component

Body Length:

Between 6.200 inches and 6.700 inches

Body Width:

Between 5.500 inches and 5.900 inches

Body Height:

Between 6.700 inches and 7.100 inches

Maximum Operating Temp:

130.0 degrees celsius

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Slot single group

Winding Function And Quantity:

1 primary single component and 6 secondary single component

Winding Operating Current:

50.0 milliamperes dc single component 1st secondary

Winding Power Rating:

407.0 volts-amperes single component 4th secondary

Winding Operating Voltage:

68.00 dc volts single component 3rd secondary

Special Features:

One primary winding; six secondary windings, first, second, fourth, fifth, and sixth windings center tapped

Terminal Type And Quantity:

23 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0