

View Online at <https://aerobasegroup.com/nsn/5950-01-159-5561>

**Reliability Indicator:**

Not established

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

4.610 inches single mounting facility single center group and 4.630 inches single mounting facility single center group

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

4.930 inches single mounting facility single center group and 4.950 inches single mounting facility single center group

**Mounting Slot Width:**

0.240 inches single group and 0.300 inches single group

**Frequency Rating:**

57.0 hertz single component and 63.0 hertz single component

**Input-output Phase Relationship:**

Single phase to single phase single component

**Winding Shielding Method:**

Internal shield grounded to inclosure single component

**Body Length:**

Between 6.200 inches and 6.700 inches

**Body Width:**

Between 5.500 inches and 5.900 inches

**Body Height:**

Between 6.700 inches and 7.100 inches

**Maximum Operating Temp:**

130.0 degrees celsius

**Inclosure Type:**

Fully enclosed

**Mounting Facility Quantity:**

4 single group

**Mounting Method:**

Slot single group

**Winding Function And Quantity:**

1 primary single component and 6 secondary single component

**Winding Operating Current:**

50.0 milliamperes dc single component 1st secondary

**Winding Power Rating:**

407.0 volts-amperes single component 4th secondary

**Winding Operating Voltage:**

68.00 dc volts single component 3rd secondary

**Special Features:**

One primary winding; six secondary windings, first, second, fourth, fifth, and sixth windings center tapped

**Terminal Type And Quantity:**

23 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A058b0