

View Online at <https://aerobasegroup.com/nsn/5950-01-159-5562>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

5.270 inches single mounting facility single center group and 5.470 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

4.200 inches single mounting facility single center group and 4.400 inches single mounting facility single center group

Mounting Slot Width:

0.270 inches single group

Frequency Rating:

57.0 hertz single component and 63.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internal shield grounded to inclosure single component

Body Length:

Between 6.400 inches and 6.800 inches

Body Width:

Between 5.600 inches and 6.400 inches

Body Height:

Between 5.200 inches and 5.600 inches

Maximum Operating Temp:

130.0 degrees celsius

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Slot single group

Winding Function And Quantity:

1 primary single component and 3 secondary single component

Features Provided:

W/rectifier

Winding Operating Current:

50.0 milliamperes dc single component 1st secondary

Winding Operating Voltage:

37.00 ac volts single component 2nd secondary

Terminal Type And Quantity:

13 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0