

View Online at <https://aerobasegroup.com/nsn/5950-01-163-9262>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.173 inches single mounting facility single center group and 1.203 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.173 inches single mounting facility single center group and 1.203 inches single mounting facility single center group

Frequency Rating:

50.0 hertz single component or 60.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Body Length:

Between 1.560 inches and 1.620 inches

Body Width:

Between 1.560 inches and 1.620 inches

Body Height:

Between 2.260 inches and 2.380 inches

Maximum Operating Temp:

105.0 degrees celsius

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded stud single group

Winding Function And Quantity:

1 primary single component and 1 secondary single component

Thread Size:

0.138 inches single group

Winding Operating Current:

600.0 milliamperes ac single component single secondary

Winding Power Rating:

3.8 volts-amperes single component single secondary

Winding Operating Voltage:

6.30 ac volts single component single secondary

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

7 turret

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0