

View Online at <https://aerobasegroup.com/nsn/5950-01-164-0322>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

3.500 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

3.250 inches single mounting facility single center group

Overall Height:

4.380 inches

Inductance Type:

Fixed

Frequency Rating:

400.0 hertz single component

Body Length:

4.500 inches

Body Width:

4.000 inches

Body Height:

3.500 inches

Maximum Operating Temp:

155.0 degrees celsius

End Application:

Wsd: ticonderoga class cg (47); spruance class dd (963); oliver perry class ffg; arleigh burke class ddg; an/sqq-89 surface ship asw combat system

Winding Quantity:

1 single component

Inclosure Type:

Open

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded hole single group

Rating Method:

Electrical single component single winding

Thready Qty Per Inch (tpi):

32 single group

Thread Size:

0.190 inches single group

Winding Operating Current:

3.0 amperes ac single component single winding

Dc Resistance Rating In Ohms:

0.0014 single component single winding

Criticality Code Justification:

Feat

Special Features:

Weapon system essential

Thread Series Designator:

Unf single group

Terminal Type And Quantity:

3 threaded stud

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0