

View Online at <https://aerobasegroup.com/nsn/5950-01-165-3955>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

3.125 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.250 inches single mounting facility single center group

Frequency Rating:

400.0 hertz single component

Input-output Phase Relationship:

Three phase to three phase single component

Transformer Winding Connection Type:

Delta-wye

Winding Shielding Method:

Primary and secondary shielded and brought out to terminal single component

Body Length:

3.690 inches

Body Width:

1.790 inches

Body Height:

2.880 inches

Maximum Operating Temp:

110.0 degrees celsius

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded hole single group

Winding Function And Quantity:

1 primary single component and 1 secondary single component

Thread Size:

0.164 inches single group

Winding Operating Current:

41.0 milliamperes ac single component single secondary

Winding Operating Voltage:

187.20 ac volts single component single primary and 228.80 ac volts single component single primary

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

8 turret

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0