NSN 5950-01-165-3957

Power Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-01-165-3957

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

0.860 inches single mounting facility single center group and 0.890 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

0.610 inches single mounting facility single center group and 0.640 inches single mounting facility single center group

Overall Height:

2.440 inches

Overall Width:

1.175 inches

Frequency Rating:

400.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internally shielded grounded to core and mounting single component

Body Length:

1.450 inches

Maximum Operating Temp:

71.0 degrees celsius

End Application:

1430-01-087-6330; missile, patriot

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded hole single group

Winding Function And Quantity:

1 primary single component and 2 secondary single component

Thread Size:

0.164 inches single group

Winding Operating Current:

88.0 milliamperes ac single component 1st secondary

Winding Operating Voltage:

44.00 ac volts single component 1st secondary

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

7 tab, solder lug

Shelf Life:

N/a

NSN 5950-01-165-3957

Power Transformer - Page 2 of 2



ш	ın	10	<i>(</i>)+	Measure:	

--

Demilitarization:

No

Fiig:

A058b0