

View Online at <https://aerobasegroup.com/nsn/5950-01-166-5564>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

5.500 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

3.750 inches single mounting facility single center group

Frequency Rating:

50.0 hertz single component and 65.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internal shield grounded to inclosure and core single component

Body Length:

6.000 inches

Body Width:

3.000 inches

Body Height:

4.500 inches

Inclosure Type:

Partially enclosed, double shell

Mounting Facility Quantity:

4 single group

Mounting Method:

Unthreaded stud single group

Winding Function And Quantity:

2 primary single component and 1 secondary single component

Thread Size:

0.190 inches single group

Winding Operating Current:

420.0 milliamperes dc single component single secondary

Winding Operating Voltage:

115.00 ac volts single component all primary

Special Features:

Rectified current rating

Thread Series Designator:

Unf single group

Terminal Type And Quantity:

6 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0