NSN 5950-01-167-5124

Reactor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5950-01-167-5124

Mounting Hole Diameter: 0.144 inches single group Inductance Rating: 50.00 millihenries single component all winding Frequency Rating: 400.0 hertz single component Overall Diameter: 1.327 inches Winding Quantity: 2 single component Inclosure Type: Fully enclosed Mounting Facility Quantity: 1 single group Mounting Method: Unthreaded hole single group Winding Operating Current: 172.0 milliamperes ac single component 1st winding Dc Resistance Rating In Ohms: 2.000 single component 2nd winding Terminal Type And Quantity:
Inductance Rating: 50.00 millihenries single component all winding Frequency Rating: 400.0 hertz single component Overall Diameter: 1.327 inches Winding Quantity: 2 single component Inclosure Type: Fully enclosed Mounting Facility Quantity: 1 single group Mounting Method: Unthreaded hole single group Winding Operating Current: 172.0 milliamperes ac single component 1st winding Dc Resistance Rating In Ohms: 2.000 single component 2nd winding
Inductance Rating: 50.00 millihenries single component all winding Frequency Rating: 400.0 hertz single component Overall Diameter: 1.327 inches Winding Quantity: 2 single component Inclosure Type: Fully enclosed Mounting Facility Quantity: 1 single group Mounting Method: Unthreaded hole single group Winding Operating Current: 172.0 milliamperes ac single component 1st winding Dc Resistance Rating In Ohms: 2.000 single component 2nd winding
Frequency Rating: 400.0 hertz single component Overall Diameter: 1.327 inches Winding Quantity: 2 single component Inclosure Type: Fully enclosed Mounting Facility Quantity: 1 single group Mounting Method: Unthreaded hole single group Winding Operating Current: 172.0 milliamperes ac single component 1st winding Dc Resistance Rating In Ohms: 2.000 single component 2nd winding
Frequency Rating: 400.0 hertz single component Overall Diameter: 1.327 inches Winding Quantity: 2 single component Inclosure Type: Fully enclosed Mounting Facility Quantity: 1 single group Mounting Method: Unthreaded hole single group Winding Operating Current: 172.0 milliamperes ac single component 1st winding Dc Resistance Rating In Ohms: 2.000 single component 2nd winding
400.0 hertz single component Overall Diameter: 1.327 inches Winding Quantity: 2 single component Inclosure Type: Fully enclosed Mounting Facility Quantity: 1 single group Mounting Method: Unthreaded hole single group Winding Operating Current: 172.0 milliamperes ac single component 1st winding Dc Resistance Rating In Ohms: 2.000 single component 2nd winding
Overall Diameter: 1.327 inches Winding Quantity: 2 single component Inclosure Type: Fully enclosed Mounting Facility Quantity: 1 single group Mounting Method: Unthreaded hole single group Winding Operating Current: 172.0 milliamperes ac single component 1st winding Dc Resistance Rating In Ohms: 2.000 single component 2nd winding
1.327 inches Winding Quantity: 2 single component Inclosure Type: Fully enclosed Mounting Facility Quantity: 1 single group Mounting Method: Unthreaded hole single group Winding Operating Current: 172.0 milliamperes ac single component 1st winding Dc Resistance Rating In Ohms: 2.000 single component 2nd winding
Winding Quantity: 2 single component Inclosure Type: Fully enclosed Mounting Facility Quantity: 1 single group Mounting Method: Unthreaded hole single group Winding Operating Current: 172.0 milliamperes ac single component 1st winding Dc Resistance Rating In Ohms: 2.000 single component 2nd winding
2 single component Inclosure Type: Fully enclosed Mounting Facility Quantity: 1 single group Mounting Method: Unthreaded hole single group Winding Operating Current: 172.0 milliamperes ac single component 1st winding Dc Resistance Rating In Ohms: 2.000 single component 2nd winding
Inclosure Type: Fully enclosed Mounting Facility Quantity: 1 single group Mounting Method: Unthreaded hole single group Winding Operating Current: 172.0 milliamperes ac single component 1st winding Dc Resistance Rating In Ohms: 2.000 single component 2nd winding
Fully enclosed Mounting Facility Quantity: 1 single group Mounting Method: Unthreaded hole single group Winding Operating Current: 172.0 milliamperes ac single component 1st winding Dc Resistance Rating In Ohms: 2.000 single component 2nd winding
Mounting Facility Quantity: 1 single group Mounting Method: Unthreaded hole single group Winding Operating Current: 172.0 milliamperes ac single component 1st winding Dc Resistance Rating In Ohms: 2.000 single component 2nd winding
1 single group Mounting Method: Unthreaded hole single group Winding Operating Current: 172.0 milliamperes ac single component 1st winding Dc Resistance Rating In Ohms: 2.000 single component 2nd winding
Mounting Method: Unthreaded hole single group Winding Operating Current: 172.0 milliamperes ac single component 1st winding Dc Resistance Rating In Ohms: 2.000 single component 2nd winding
Unthreaded hole single group Winding Operating Current: 172.0 milliamperes ac single component 1st winding Dc Resistance Rating In Ohms: 2.000 single component 2nd winding
Winding Operating Current: 172.0 milliamperes ac single component 1st winding Dc Resistance Rating In Ohms: 2.000 single component 2nd winding
172.0 milliamperes ac single component 1st winding Dc Resistance Rating In Ohms: 2.000 single component 2nd winding
Dc Resistance Rating In Ohms: 2.000 single component 2nd winding
2.000 single component 2nd winding
Terminal Type And Quantity:
4 turret
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A058b0