

View Online at <https://aerobasegroup.com/nsn/5950-01-167-8078>

**Reliability Indicator:**

Not established

**Hazardous Locations/environmental Protection:**

Humidity resistant and vibration resistant

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

7.000 inches single mounting facility single center group

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

6.680 inches single mounting facility single center group

**Mounting Slot Width:**

0.440 inches single group

**Frequency Rating:**

50.0 hertz single component or 60.0 hertz single component

**Input-output Phase Relationship:**

Three phase to three phase single component and three phase to single phase single component

**Transformer Winding Connection Type:**

Wye-wye

**Maximum Transformer Power Rating:**

6.5 kilovolt-ampere single component

**Body Length:**

10.500 inches

**Body Width:**

8.600 inches

**Body Height:**

11.500 inches

**Maximum Operating Temp:**

130.0 degrees celsius

**Inclosure Type:**

Fully enclosed

**Mounting Facility Quantity:**

4 single group

**Mounting Method:**

Slot single group

**Winding Function And Quantity:**

1 primary single component and 3 secondary single component

**Winding Operating Current:**

8.0 amperes ac single component 1st secondary

**Winding Operating Voltage:**

28.00 dc volts single component 3rd secondary

**Terminal Type And Quantity:**

44 threaded hole

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A058b0