

View Online at <https://aerobasegroup.com/nsn/5950-01-167-8078>

Reliability Indicator:

Not established

Hazardous Locations/environmental Protection:

Humidity resistant and vibration resistant

Center To Center Distance Between Mounting Facilities Parallel To Length:

7.000 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

6.680 inches single mounting facility single center group

Mounting Slot Width:

0.440 inches single group

Frequency Rating:

50.0 hertz single component or 60.0 hertz single component

Input-output Phase Relationship:

Three phase to three phase single component and three phase to single phase single component

Transformer Winding Connection Type:

Wye-wye

Maximum Transformer Power Rating:

6.5 kilovolt-ampere single component

Body Length:

10.500 inches

Body Width:

8.600 inches

Body Height:

11.500 inches

Maximum Operating Temp:

130.0 degrees celsius

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Slot single group

Winding Function And Quantity:

1 primary single component and 3 secondary single component

Winding Operating Current:

8.0 amperes ac single component 1st secondary

Winding Operating Voltage:

28.00 dc volts single component 3rd secondary

Terminal Type And Quantity:

44 threaded hole

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0