# NSN 5950-01-167-9093

Power Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-01-167-9093

# Reliability Indicator:

Not established

## **Overall Length:**

3.000 inches

# **Frequency Rating:**

50.0 hertz single component or 60.0 hertz single component

## Input-output Phase Relationship:

Single phase to single phase single component

## Maximum Transformer Power Rating:

380.0 volt-ampere single component

## Adjustment Device Drive Type:

Shaft single component

## **Body Length:**

2.125 inches

#### **Body Outside Diameter:**

2.812 inches

## Mounting Bolt Circle Diameter:

1.687 inches single mounting facility single center group

## End Application:

Austin ship class lpd-4 amphibious trnsport docks; wasp class lhd; tarawa class lha

## Inclosure Type:

Open

# **Mounting Facility Quantity:**

3 single group

## **Mounting Method:**

Threaded hole single group

## Winding Function And Quantity:

2 primary single component and 2 secondary single component

## Thready Qty Per Inch (tpi):

20 single group

Thread Size:

0.112 inches single group

# Winding Operating Current:

0.8 amperes ac single component 3rd secondary

# Winding Power Rating:

2.0 watts single component all primary

# Adjustment Method And Quantity:

1 adjustable control single component

# Winding Operating Voltage:

480.00 ac volts single component all primary

# **Thread Series Designator:**

Unc single group

# NSN 5950-01-167-9093

Power Transformer - Page 2 of 2



# Terminal Type And Quantity:

8 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A058b0