## NSN 5950-01-169-8231

Radio Frequency Coil - Page 1 of 2





## **Reliability Indicator:** Not established Hazardous Locations/environmental Protection: Vibration resistant **Overall Length:** Between 0.260 inches and 0.280 inches **Overall Width:** Between 0.140 inches and 0.160 inches Inductance Rating: 120.00 microhenries single component single winding **Coil Form Type:** Solid single component **Core Construction:** S0lid single component **Body Height:** Between 0.270 inches and 0.300 inches Maximum Operating Temp: 125.0 degrees celsius Inclosure Type: Fully enclosed **Mounting Method:** Terminal single group **Rating Method:** Electrical single component single winding Winding Operating Current: 160.0 milliamperes dc single component single winding **Dc Resistance Rating In Ohms:** 12.000 single component single winding **Quality Factor:** 45 single component single winding **Test Data Document:** 81349-mil-prf-15305 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). **Terminal Type And Quantity:** 2 wire lead **Specification Data:** 96906-ms21424 government standard Shelf Life: N/a Unit Of Measure: **Demilitarization:** No

## NSN 5950-01-169-8231

Radio Frequency Coil - Page 2 of 2

**Fiig:** A058b0

Mil-std (military Standard):

Mil-prf-15305 spec.

