

View Online at <https://aerobasegroup.com/nsn/5950-01-170-0534>

**Reliability Indicator:**

Not established

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

4.375 inches single mounting facility single center group

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

3.750 inches single mounting facility single center group

**Mounting Hole Diameter:**

0.210 inches single group

**Frequency Rating:**

60.0 hertz single component

**Input-output Phase Relationship:**

Single phase to single phase single component

**Maximum Transformer Power Rating:**

350.0 kilovolt-ampere single component

**Body Length:**

5.062 inches

**Body Width:**

4.750 inches

**Body Height:**

4.437 inches

**Inclosure Type:**

Fully enclosed

**Mounting Facility Quantity:**

4 single group

**Mounting Method:**

Bracket single group and unthreaded hole single group

**Winding Function And Quantity:**

1 primary single component and 3 secondary single component

**Winding Operating Current:**

10.0 amperes ac single component 3rd secondary

**Criticality Code Justification:**

Feat

**Winding Operating Voltage:**

6.00 ac volts single component 3rd secondary

**Special Features:**

Item must comply with requirements of defense supply center columbus production standard no. Lo3343

**Terminal Type And Quantity:**

9 tab, solder lug

**Reference Number Differentiating Characteristics:**

Reference number differentiating material will be in accordance with naval inventory control point activity hx quality control. Manufacturing and testing specifications available at the dla icp

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A058b0