

View Online at <https://aerobasegroup.com/nsn/5950-01-170-2041>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.545 inches single mounting facility single center group and 1.555 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.015 inches single mounting facility single center group and 1.025 inches single mounting facility single center group

Mounting Hole Diameter:

0.120 inches single group and 0.141 inches single group

Frequency Rating:

400.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internal shield brought out to terminal single component

Body Length:

Between 2.060 inches and 2.070 inches

Body Width:

Between 1.335 inches and 1.345 inches

Body Height:

Between 1.695 inches and 1.705 inches

Maximum Operating Temp:

130.0 degrees celsius

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Unthreaded hole single group

Winding Function And Quantity:

1 primary single component and 2 secondary single component

Winding Operating Current:

750.0 milliamperes ac single component 2nd secondary

Winding Operating Voltage:

38.80 ac volts single component 1st secondary

Terminal Type And Quantity:

9 wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0