## NSN 5950-01-170-4406

Radio Frequency Coil - Page 1 of 2



| view Online at https://aerobasegroup.com/hsn/5950-01-170-4406  |
|--|
| Reliability Indicator:   |
| Not established  |
| Inductance Rating:   |
| 4.70 millihenries single component single winding  |
| Coil Form Type:  |
| Solid single component   |
| Core Construction:   |
| S0lid single component   |
| Body Length:   |
| 0.335 inches   |
| Overall Diameter:  |
| 0.136 inches   |
| Maximum Operating Temp:  |
| 105.0 degrees celsius  |
| Inclosure Type:  |
| Fully enclosed   |
| Mounting Method:   |
| Terminal single group  |
| Rating Method:   |
| Electrical single component single winding   |
| Features Provided:   |
| Tinned wire leads  |
| Winding Conductor Size:  |
| 0.02010 inches american wire gage single component single winding  |
| Winding Operating Current:   |
| 27.0 milliamperes dc single component single winding   |
| Dc Resistance Rating In Ohms:  |
| 85.000 single component single winding   |
| Quality Factor:  |
| 55 single component single winding   |
| Special Features:  |
| Magneticaly shielded core  |
| Test Data Document:  |
| 81349-mil-c-15305 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification |
| format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain          |
| environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).                            |
| Terminal Type And Quantity:  |
| 2 wire lead  |
| Specification Data:  |
| 96906-ms21401 government standard  |
| Shelf Life:  |
| N/a  |

**Unit Of Measure:** 

## NSN 5950-01-170-4406

Radio Frequency Coil - Page 2 of 2



Demilitarization:

No

Fiig:

A058b0