

View Online at <https://aerobasegroup.com/nsn/5950-01-171-8776>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

2.000 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.312 inches single mounting facility single center group

Inductance Type:

Fixed

Inductance Rating:

420.00 millihenries single component single winding

Frequency Rating:

60.0 hertz single component

Body Length:

2.350 inches

Body Width:

1.650 inches

Body Height:

2.750 inches

Maximum Operating Temp:

65.0 degrees celsius

End Application:

Tarawa class lha, wasp class lhd, virginia class cgn (41), kidd class ddg, nimitz class cvn, blue ridge class lcc-19, whidbey island class lsd, ticonderoga class cg (47), forrestal class cv.

Winding Quantity:

1 single component

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded hole single group

Rating Method:

Electrical single component single winding

Thready Qty Per Inch (tpi):

32 single group

Thread Size:

0.138 inches single group

Winding Operating Current:

700.0 milliamperes dc single component single winding

Dc Resistance Rating In Ohms:

14.000 single component single winding

Criticality Code Justification:

Feat

Special Features:

Weapo system essential

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

2 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0