NSN 5950-01-171-8792



| Power Transformer - Page 1 of 2 |
|---|
| View Online at https://aerobasegroup.com/nsn/5950-01-171-8792 |
| Reliability Indicator: |
| Not established |
| Overall Length: |
| 3.375 inches |
| Center To Center Distance Between Mounting Facilities Parallel To Length: |
| 2.812 inches single mounting facility single center group |
| Center To Center Distance Between Mounting Facilities Parallel To Width: |
| 2.375 inches single mounting facility single center group |
| Overall Height: |
| 2.875 inches |
| Overall Width: |
| 3.375 inches |
| Mounting Slot Width: |
| 0.203 inches single group |
| Frequency Rating: |
| 50.0 hertz single component or 60.0 hertz single component |
| Input-output Phase Relationship: |
| Single phase to single phase single component |
| Maximum Transformer Power Rating: |
| 100.0 volt-ampere single component |
| Maximum Operating Temp: |
| 105.0 degrees celsius |
| Inclosure Type: |
| Partially enclosed, double shell |
| Mounting Facility Quantity: |
| 4 single group |
| Mounting Method: |
| Slot single group |

Winding Function And Quantity:

1 primary single component and 1 secondary single component

Thread Size:

0.190 inches single group

Winding Operating Current:

4.2 amperes ac single component single secondary

Winding Operating Voltage:

24.00 ac volts single component single secondary

Thread Series Designator:

Unf single group

Terminal Type And Quantity:

2 terminal block w/screws

Shelf Life:

N/a

NSN 5950-01-171-8792

Power Transformer - Page 2 of 2



| | • • | | | | |
|----|-----|-------------|-----|-----|------|
| In | 18 | <i>(</i>)+ | МЛО | 201 | ure: |
| | | | | | |

--

Demilitarization:

No

Fiig:

A058b0