

View Online at <https://aerobasegroup.com/nsn/5950-01-172-4208>

Reliability Indicator:

Not established

Overall Length:

1.630 inches

Mounting Hole Diameter:

0.110 inches single group and 0.140 inches single group

Frequency Rating:

400.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internal shield grounded to core single component

Body Width:

0.940 inches

Body Height:

0.880 inches

Distance Between Mounting Facility Centers:

1.360 inches single mounting facility single center group and 1.390 inches single mounting facility single center group

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

2 single group

Mounting Method:

Unthreaded hole single group

Winding Function And Quantity:

1 primary single component and 1 secondary single component

Winding Operating Current:

50.0 milliamperes dc single component single secondary and 150.0 milliamperes dc single component single secondary

Winding Power Rating:

2.4 volts-amperes single component single secondary

Winding Operating Voltage:

5.00 dc volts single component single secondary and 27.00 dc volts single component single secondary and 32.00 dc volts single component single secondary

Terminal Type And Quantity:

7 wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0