NSN 5950-01-172-7394

Power Transformer - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5950-01-172-7394

| D | ام | ia | h | ii | i٤٠ | , 1 | ın | ч | i | са | 4 | _ | r | |
|---|----|----|---|----|-----|------------|----|---|---|----|---|---|---|--|
| к | еı | ıα | D | Ш | IU | 7 I | Ш | u | ı | Ca | τ | U | Г | |

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

5.995 inches single mounting facility single center group and 6.005 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

2.495 inches single mounting facility single center group and 2.505 inches single mounting facility single center group

Mounting Slot Width:

0.188 inches single group

Frequency Rating:

60.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Maximum Transformer Power Rating:

300.0 volt-ampere single component

Body Length:

Between 6.645 inches and 6.755 inches

Body Width:

Between 4.433 inches and 4.453 inches

Body Height:

Between 4.745 inches and 4.755 inches

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

6 single group

Mounting Method:

Slot single group

Winding Function And Quantity:

1 primary single component and 1 secondary single component

Winding Operating Current:

20.0 milliamperes ac single component single secondary

Winding Operating Voltage:

120.00 ac pounds per hour wet single component single primary

Terminal Type And Quantity:

2 connector, plug and 2 wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0