

View Online at <https://aerobasegroup.com/nsn/5950-01-172-8564>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

4.370 inches single mounting facility single center group and 4.380 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

3.495 inches single mounting facility single center group and 3.505 inches single mounting facility single center group

Mounting Hole Diameter:

0.280 inches single group and 0.288 inches single group

Frequency Rating:

60.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internal shield brought out to terminal single component

Body Length:

Between 5.200 inches and 5.300 inches

Body Width:

Between 4.330 inches and 4.430 inches

Body Height:

4.540 inches

Maximum Operating Temp:

130.0 degrees celsius

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Unthreaded hole single group

Winding Function And Quantity:

1 primary single component and 1 secondary single component

Winding Operating Current:

6.0 amperes ac single component single secondary

Winding Operating Voltage:

6.00 ac volts single component single secondary and 115.00 ac volts single component single secondary

Terminal Type And Quantity:

6 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0