

View Online at <https://aerobasegroup.com/nsn/5950-01-174-7691>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

3.125 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

2.250 inches single mounting facility single center group

Overall Height:

2.409 inches

Frequency Rating:

400.0 hertz single component

Input-output Phase Relationship:

Three phase to three phase single component

Transformer Winding Connection Type:

Delta-delta

Maximum Transformer Power Rating:

221.4 volt-ampere single component

Winding Shielding Method:

Internal shield brought out to terminal single component

Body Length:

3.780 inches

Body Width:

2.900 inches

Maximum Operating Temp:

155.0 degrees celsius

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded hole single group

Winding Function And Quantity:

1 primary single component and 5 secondary single component

Thread Size:

0.190 inches single group

Winding Operating Current:

650.0 milliamperes dc single component 3rd secondary

Winding Power Rating:

36.2 volts-amperes single component 4th secondary

Winding Operating Voltage:

17.00 ac volts single component 1st secondary

Special Features:

One primary and five secondaries

Thread Series Designator:

Unf single group

Terminal Type And Quantity:

19 turret

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0