# NSN 5950-01-174-7691

Power Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-01-174-7691

# **Reliability Indicator:**

Not established

#### Center To Center Distance Between Mounting Facilities Parallel To Length:

3.125 inches single mounting facility single center group

#### **Center To Center Distance Between Mounting Facilities Parallel To Width:**

2.250 inches single mounting facility single center group

#### **Overall Height:**

2.409 inches

#### **Frequency Rating:**

400.0 hertz single component

#### Input-output Phase Relationship:

Three phase to three phase single component

#### **Transformer Winding Connection Type:**

Delta-delta

#### **Maximum Transformer Power Rating:**

221.4 volt-ampere single component

# **Winding Shielding Method:**

Internal shield brought out to terminal single component

# **Body Length:**

3.780 inches

# **Body Width:**

2.900 inches

#### **Maximum Operating Temp:**

155.0 degrees celsius

# **Inclosure Type:**

Fully enclosed

# **Mounting Facility Quantity:**

4 single group

#### **Mounting Method:**

Threaded hole single group

# **Winding Function And Quantity:**

1 primary single component and 5 secondary single component

# **Thread Size:**

0.190 inches single group

# **Winding Operating Current:**

650.0 milliamperes dc single component 3rd secondary

# Winding Power Rating:

36.2 volts-amperes single component 4th secondary

# **Winding Operating Voltage:**

17.00 ac volts single component 1st secondary

#### **Special Features:**

One primary and five secondaries

# **NSN 5950-01-174-7691**Power Transformer - Page 2 of 2



Inread Series Designator:
Unf single group
Terminal Type And Quantity:
19 turret
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A058b0