NSN 5950-01-175-0044

Power Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-01-175-0044

Reliability Indicator: Not established Hazardous Locations/environmental Protection: Vibration resistant Overall Length: Between 1.250 inches and 1.312 inches Overall Height: 2.380 inches Overall Width: Between 1.250 inches and 1.312 inches Frequency Rating: 400.0 hertz single component
Hazardous Locations/environmental Protection: Vibration resistant Overall Length: Between 1.250 inches and 1.312 inches Overall Height: 2.380 inches Overall Width: Between 1.250 inches and 1.312 inches Frequency Rating:
Vibration resistant Overall Length: Between 1.250 inches and 1.312 inches Overall Height: 2.380 inches Overall Width: Between 1.250 inches and 1.312 inches Frequency Rating:
Overall Length: Between 1.250 inches and 1.312 inches Overall Height: 2.380 inches Overall Width: Between 1.250 inches and 1.312 inches Frequency Rating:
Between 1.250 inches and 1.312 inches Overall Height: 2.380 inches Overall Width: Between 1.250 inches and 1.312 inches Frequency Rating:
Overall Height: 2.380 inches Overall Width: Between 1.250 inches and 1.312 inches Frequency Rating:
2.380 inches Overall Width: Between 1.250 inches and 1.312 inches Frequency Rating:
Overall Width: Between 1.250 inches and 1.312 inches Frequency Rating:
Between 1.250 inches and 1.312 inches Frequency Rating:
Frequency Rating:
• •
400.0 hertz_single component
100.0 Horse Single compension
Input-output Phase Relationship:
Single phase to single phase single component
Maximum Operating Temp:
75.0 degrees celsius
Distance Between Mounting Facility Centers:
1.234 inches single mounting facility single center group and 1.250 inches single mounting facility single center group
Inclosure Type:
Hermetically sealed
Mounting Facility Quantity:
2 single group
Mounting Method:
Threaded stud single group
Winding Function And Quantity:
1 primary single component and 1 secondary single component
Thread Size:
0.138 inches single group
Winding Operating Current:
10.0 milliamperes ac single component single secondary
Winding Operating Voltage:
2.80 ac pounds per hour wet single component single secondary
Thread Series Designator:
Unc single group
Terminal Type And Quantity:
4 threaded stud
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:

No

NSN 5950-01-175-0044

Power Transformer - Page 2 of 2



Fiig:

A058b0