## NSN 5950-01-175-2450

Power Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-01-175-2450
Reliability Indicator:
Not established
Center To Center Distance Between Mounting Facilities Parallel To Length:
1.250 inches single mounting facility single center group
Center To Center Distance Between Mounting Facilities Parallel To Width:
2.000 inches single mounting facility single center group
Frequency Rating:
4.0 kilohertz single component and 5.0 kilohertz single component
Input-output Phase Relationship:
Single phase to single phase single component
Winding Shielding Method:
Internal shield brought out to terminal single component and internal shield connected to secondary terminal single component
Body Length:
2.330 inches
Body Width:
1.750 inches
Body Height:
2.500 inches
Inclosure Type:
Fully enclosed
Mounting Facility Quantity:
4 single group
Mounting Method:
Threaded hole single group
Winding Function And Quantity:
2 primary single component and 1 secondary single component
Thread Size:
0.138 inches single group
Winding Operating Current:
500.0 milliamperes ac single component 2nd primary
Winding Power Rating:
544.0 watts single component single secondary
Winding Operating Voltage:
75.00 ac volts single component 1st primary
Thread Series Designator:
Unf single group
Terminal Type And Quantity:
13 turret
Shelf Life:
N/a

--

**Unit Of Measure:** 

## NSN 5950-01-175-2450

Power Transformer - Page 2 of 2



Demilitarization:

No

Fiig:

A058b0