

View Online at <https://aerobasegroup.com/nsn/5950-01-175-2450>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.250 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

2.000 inches single mounting facility single center group

Frequency Rating:

4.0 kilohertz single component and 5.0 kilohertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internal shield brought out to terminal single component and internal shield connected to secondary terminal single component

Body Length:

2.330 inches

Body Width:

1.750 inches

Body Height:

2.500 inches

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded hole single group

Winding Function And Quantity:

2 primary single component and 1 secondary single component

Thread Size:

0.138 inches single group

Winding Operating Current:

500.0 milliamperes ac single component 2nd primary

Winding Power Rating:

544.0 watts single component single secondary

Winding Operating Voltage:

75.00 ac volts single component 1st primary

Thread Series Designator:

Unf single group

Terminal Type And Quantity:

13 turret

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0