## NSN 5950-01-175-9838

Power Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-01-175-9838

## **Reliability Indicator:**

Not established

#### Center To Center Distance Between Mounting Facilities Parallel To Length:

5.625 inches single mounting facility single center group

#### Center To Center Distance Between Mounting Facilities Parallel To Width:

2.500 inches single mounting facility single center group

#### Frequency Rating:

400.0 hertz single component

#### Input-output Phase Relationship:

Three phase to three phase single component

#### **Transformer Winding Connection Type:**

Delta-delta

#### **Maximum Transformer Power Rating:**

1.3 kilovolt-ampere single component

#### **Winding Shielding Method:**

Internal shield grounded to core single component

#### **Body Length:**

8.250 inches

#### **Body Width:**

3.250 inches

### **Body Height:**

4.812 inches

#### **Maximum Operating Temp:**

43.0 degrees celsius

### **Inclosure Type:**

Fully enclosed

## **Mounting Facility Quantity:**

4 single group

#### **Mounting Method:**

Threaded hole single group

## **Winding Function And Quantity:**

1 primary single component and 1 secondary single component

## **Thread Size:**

0.250 inches single group

#### **Winding Operating Current:**

6.5 amperes ac single component single secondary

## **Winding Operating Voltage:**

115.00 ac volts single component single secondary

#### **Thread Series Designator:**

Unc single group

#### **Terminal Type And Quantity:**

6 threaded stud

# NSN 5950-01-175-9838

Power Transformer - Page 2 of 2



_					
c	hο	JIF.		.ife:	
J			_	.II C.	

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A058b0