

View Online at <https://aerobasegroup.com/nsn/5950-01-176-4965>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.375 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.250 inches single mounting facility single center group

Frequency Rating:

60.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Maximum Transformer Power Rating:

40.0 volt-ampere single component

Body Length:

1.875 inches

Body Width:

1.750 inches

Body Height:

2.719 inches

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded stud single group

Winding Function And Quantity:

1 primary single component and 1 secondary single component

Features Provided:

W/rectifier

Thread Size:

0.138 inches single group

Winding Operating Current:

290.0 milliamperes ac single component single primary

Winding Power Rating:

33.5 volts-amperes single component single primary

Winding Operating Voltage:

32.50 ac volts single component single secondary

Special Features:

Rectifier connected to secondary and brought out to two terminals

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

6 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0